

## Polished Rod

Polished rod is an important part for connecting pump unites to sucker rod string in rod-pumping system. WE provides all kinds of [polished rod](#), which is featured with high strength, good toughness, smooth surface, and long service life. Low - and medium - alloy steel polished rods with an excellent surface finish to ensure the proper seal in the stuffing box, produced under API standards for lengths up to 36 ft. Polished, chromed and metalized options available.

### General Features



GG series Polished Rod are important parts for connecting pump unites to sucker rod string in rod-pumping system. Suitable for onshore oil production.

### Details

The GG series polished rods were developed to provide the market with more reliable technology and more hoisting performance. Polished Rod are important parts for connecting pump unites to sucker rod string in rod-pumping system. Featured with high strength, good toughness, smooth surface, and long service life. Included but not limited by the advantages mentioned, GG series polished rods might be your best choice.

### General Features

- Hook manufactured according to API 11B
- Suitable for cold area and desert environment
- Suitable for onshore oil production
- Multiple type for selection
- Featured with high strength, good toughness, smooth surface, and long service life

## Main aramaters

Size: 1-1/8" – 1-1/2" (28.6 mm – 38.1 mm)

### Parameters:

Type	Size (in)	Rod OD (in)	Thread (in)	Rod Length (ft)	Sucker Rod Size (in)
Standard	1-1 /8	1-1 /8	5/16	8, 11, 16, 22, 24, 26	5/8
			1-1 /16		3/4
	1-1 /4	1-1 /4	3-1 /16		5/8
	1-1 /2	1-1 /2	3-1 /8		1
One end upset	1-1 /8	1-1 /8	15/16	8, 11, 16, 22, 24, 26	5/8
			1-1 /16		3/4
	1-1 /4	1-1 /4	3-1 /16		7/8