

Fittings

Fittings are parts that change direction in the transference in a pipe system, connect and joint piping and/or equipment, and to block or regulate flow in a piping system. The J series pipe fittings were developed to provide the market with more reliable technology and more hoisting performance. Full size for choose, reliable quality and reasonable price. Included but not limited by the advantages mentioned, J series pipe fittings might be your best choice

General Features



J series Pipe Fittings are standard high quality products. Suitable for onshore or offshore pipeline, petrochemical projects.

Details

The J series pipe fittings were developed to provide the market with more reliable technology and more hoisting performance. Full size for choose, reliable quality and reasonable price. Included but not limited by the advantages mentioned, J series pipe fittings might be your best choice.

General Features

- Suitable for onshore or offshore operations
- High strength steel, provide reliable quality

Main aramaters

Size: 1-1/2" – 24" (38 mm – 610 mm)

Parameters:

Casing Coupling for Round thread

Size (in)	O.D. (in)	Minimum Length (in)		Weight (lb)	
		Short	Long	Short	Long
4-1/2	5.000	6-1/4	7	7.98	9.16
5	5.563	6-1/2	7-3/4	10.27	12.68
5-1/2	6.050	6-3/4	8	11.54	14.15
6-5/8	7.390	7-1/4	8-3/4	20.11	25.01
7	7.656	7-1/4	9	18.49	23.87
7-5/8	8.500	7-1/2	9-1/4	27.11	34.46
8-5/8	9.625	7-3/4	10	35.79	47.77
9-5/8	10.625	7-3/4	10-1/2	39.75	56.11
10-3/4	11.750	8	–	45.81	–
11-3/4	12.750	8	–	49.91	–
13-5/8	14.375	8	–	56.57	–
16	17.000	9	–	76.96	–
18-5/8	20.000	9	–	119.07	–
20	21.000	9	11-1/2	95.73	126.87

Casing Coupling for Buttress thread

Size (in)	O.D. (in)	Minimum Length (in)	Weight (lb)
4-1/2	5.000	8-7/8	10.12
5	5.563	9-1/8	13.00
5-1/2	6.050	9-1/4	14.15
6-5/8	7.390	9-5/8	24.49
7	7.656	10	23.24
7-5/8	8.500	10-3/8	34.88
8-5/8	9.625	10-5/8	45.99
9-5/8	10.625	10-5/8	51.05
10-3/4	11.750	10-5/8	56.74
11-3/4	12.750	10-5/8	61.80
13-5/8	14.375	10-5/8	70.03
16	17.000	10-5/8	88.81
18-5/8	20.000	10-5/8	138.18
20	21.000	10-5/8	110.45

Tubing Coupling

Size (in)	O.D. (in)	Minimum Length (in)	Weight (lb)
2-3/8	2.875	4-1/4	2.82
2-7/8	3.500	5-1/8	5.15
3-1/2	4.250	5-5/8	8.17
4	4.750	5-3/4	9.58
4-1/2	5.200	6-1/8	10.77

Other Fittings

Please contact us for details.